

Série HRB – 4

Dados Técnicos:

	Comprimento Curvado l (mm)	Ø D min = ødx3		Ø Rolo Superior ød (mm)	Ø Rolo Inferior ød (mm)	Ø Rolos Laterais ø (mm)	Potência Motor kW	Comprimento (mm)	Largura (mm)	Altura (mm)	Peso (Kg)
		Capacidade Pré-Curvado t (mm)	Capacidade Curvado (mm)								
		HRB – 4 2006	2050								
HRB – 4 2008	2050	6	8	200	180	170	5.5	3850	1300	1150	3900
HRB – 4 2010	2050	8	10	210	190	180	7.5	3950	1400	1150	4300
HRB – 4 2013	2050	10	13	230	210	190	7.5	3950	1400	1150	5300
HRB – 4 2016	2050	13	16	270	250	220	11	4150	1650	1400	6500
HRB – 4 2020	2050	16	20	300	270	220	11	4150	1650	1400	8000
HRB – 4 2025	2050	20	25	330	300	250	15	4350	1900	1700	10500
HRB – 4 2030	2050	25	30	360	330	250	18.5	4350	1900	1700	11200
HRB – 4 2035	2050	30	35	400	370	300	22	4950	2100	1900	14000

HRB – 4 2506	2550	4	6	200	180	170	5.5	4350	1300	1150	4300
HRB – 4 2508	2550	6	8	210	190	180	7.5	4450	1400	1150	4800
HRB – 4 2510	2550	8	10	230	210	190	7.5	4450	1400	1150	6000
HRB – 4 2513	2550	10	13	270	250	220	11	4650	1650	1400	7200
HRB – 4 2516	2550	13	16	300	270	220	11	4650	1650	1400	8800
HRB – 4 2520	2550	16	20	330	300	250	15	4850	1900	1700	10200
HRB – 4 2525	2550	20	25	360	330	250	18.5	4850	1900	1700	12500

HRB – 4 3006	3100	4	6	210	190	180	7.5	5000	1400	1150	5300
HRB – 4 3008	3100	6	8	230	210	190	7.5	5000	1400	1150	6500
HRB – 4 3010	3100	8	10	270	250	220	11	5200	1650	1400	8500
HRB – 4 3013	3100	10	13	300	270	220	11	5200	1650	1400	9700
HRB – 4 3016	3100	13	16	330	300	250	15	5400	1900	1700	12200
HRB – 4 3020	3100	16	20	360	330	250	18.5	5400	1900	1700	14000
HRB – 4 3025	3100	20	25	400	370	300	22	6000	2100	1900	18000
HRB – 4 3030	3100	25	30	430	400	330	30	6000	2200	2000	24000
HRB – 4 3035	3100	30	35	450	420	360	37	6500	2300	2200	30000
HRB – 4 3040	3100	35	40	470	430	360	37	6500	2300	2200	33000
HRB – 4 3050	3100	40	50	520	490	420	55	6700	2700	2500	45000
HRB – 4 3065	3100	50	65	650	600	500	66	7300	3600	3650	74000

HRB – 4 4008	4100	6	8	300	270	220	11	6200	1650	1400	12200
HRB – 4 4013	4100	10	13	360	330	250	18.5	6400	1900	1700	16500
HRB – 4 4016	4100	12	15	400	370	300	22	7000	2100	1900	20000